

HANDRAIL BRACKET INSTALLATION INSTRUCTIONS

Black line backside the mounting plate indicates the angle of Bracket

For SURFACE MOUNT installation:

- Screw mounting plate into wall with supplied screws.
- Attach the rosette to the mounting plate by simply pushing it in to place.
- Screw in the bracket onto the screw that comes out of the mounting plate until it is fairly tight and in position.
- Tighten up the set screw on bracket
- Attach rail to the bracket with supplied screws.

For GLASS installation:

- Drill a 12mm hole into glass in the appropriate position.
- Slide the screw that is attached to the mounting plate through the backside of the glass using plastic washers that are provided.
- Screw on the front mounting plate to the bolt coming through the glass.
- Attach the rosettes to the front and back mounting plates.
- Screw in the bracket onto the screw that comes out of the mounting plate until it is fairly tight and in position.
- Tighten up the set screw on bracket
- Attach rail to the bracket with supplied screws.

For CONCRETE installation:

- Drill a 12mm hole into the concrete in the appropriate position.
- Insert concrete anchor into the hole and tighten until it is good and snug.
- Screw on front mounting plate to the bolt sticking out of the concrete.
- Attach the rosette to this plate.
- Screw in the bracket onto the screw that comes out of the mounting plate until it is fairly tight and in position.
- Tighten up the set screw on the bracket.
- Attach rail to the bracket with supplied screws.