


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	PLA160ST-RT	INSIDE TRIM	1
2	PLA160RT-O	OUTSIDE TRIM	1
3	PLM50RR	MORTISE LOCK	1
4	PLOVSCR45	M4 MACHINE SCREW	2
5	SPDL31	SPINDLE 1 3/8 DOOR	1
6	SPDL41	SPINDLE 1 3/4 DOOR	1
7	PL-FP50	FRAME PLATE	1
8	PL-KNPVT	PIVOT KNOB	1
9	PL-KNSTR	STRAIGHT KNOB	1
10	PL-KNADA	ADA KNOB	1
11	PL-STK50	STRIKE PLATE	1
12	PL-DB50	DUST BOX	1
13	PL-CCLIPS	SNAP RING	2
14	PL-160ER	EMERGENCY RELEASE BUTTON	1
15	#8 x 3/4" WOOD SCREW		4

Linnea[®]

www.linnea-home.com Toll Free 800-219-2366 Ph 770-559-9035


PL160R-PR

ALIGN WITH CENTER OF DOOR FRAME




MEASUREMENTS ARE IN INCHES AND MILLIMETERS
INCHES ARE SHOWN IN []

ALIGN WITH CENTER OF DOOR




PRINT THIS PAGE AT 100% SCALE

1 3/4" DOOR THICKNESS




ALGIN WITH CENTER OF DOOR FRAME




MEASUREMENTS ARE IN INCHES AND MILLIMETERS
INCHES ARE SHOWN IN []

ALGIN WITH CENTER OF DOOR




PRINT THIS PAGE AT 100% SCALE

1 3/8" DOOR THICKNESS




Print template full scale
paper template.
Drill 3.175 mm [1/8"]
on door center
943.4mm [37 9/64"]
above floor

STEP 1




Print template full scale
fold and position on door.
Use hole saw to drill
39.68 mm [1 9/16"]
through door.

Print template full scale
fold and position on door.
Use hole saw to drill
39.68 mm [1 9/16"]
through door 944.5mm [37 3/16"]
above floor.



STEP 2


CUT OVAL
THROUGH DOOR



STEP 3

MORTISE FACE PLATE
3.5mm DEEP

STEP 4



MORTISE LOCK BODY
72mm DEEP

STEP 5

